

## Automated Counterbalanced Narrow Aisle Forklift **R-MATIC 3,500 lb. Capacity**

The Linde R-MATIC is the automated narrow aisle counterbalanced forklift specializing in high-level narrow aisle storage.

Automated Guided Forklifts [AGF's] are the future of efficient material flows. They mitigate labor market dependency, take over repetitive transport tasks, increase throughput volume, and reduce the error and accident rates in the warehouse. Linde Automation offers a wide range of cutting-edge automation solutions for pallet handling warehouse trucks from the MATIC series. All models are platformed on series manufactured trucks with integrated intelligent navigation, safety technology, and software.

- → The Linde R-MATIC is a counter-balanced moving-mast narrow aisle truck designed to move loads up to 3,500 lbs with lifting capabilities up to 33 ft.
- → It is frequently used in pallet storage applications of raw materials, packaging materials, work in process, and finished goods.
- → R-Matic fleets are commonly used for multi-tier selective racking applications, block storage, gravity (FIFO) racking, and multi-deep shuttle racking (LIFO & FIFO).
- → R-Matic systems can handle versatile load profiles and combine high lifting capabilities with the flexibility of handling diverse and complex applications.



## LINDE R-MATIC

Pallet positioning scanner

Characteristics	Manufacturer		LINDE
	Manufacturer's type designation		R - Matic
	Power unit		Battery
	Load capacity/Load	(lb)	3,500
	Mast Lift Height: typically	(ft)	23 - 33
	Overall size (LxW):	(in)	102 - 56.7
	Minimal operating aisle width with GMA pallet	(in)	126-146
	Standard battery Voltage/Rated Capacity	(V) (Ah) PbS	48 / 465-775
	Navigation		Laser hybrid navigation
	Laser navigation scan height	(in)	98
	Lowered mast height		Subject to application
	Max floor incline		Subject to application
	Operation capability		Automated + Manual auxiliary operation
	Travel speed	(mph)	3.8
	Principal equipment compliance standards/norms		ANSI B56.5 Part III
			Machinery Directive (CE) requirements
			ISO3691-4 standard
common options	Blue Spot		
	Automatic opportunity charging		
	Curtain scanner front and/or sides		



For more information on Linde Material Handling equipment, please contact:

KION North America Corporation 2450 West 5th North Street, Summerville, SC 29483 Phone: (843) 875.8000 Truck Sales Fax: (843) 875.8471 Email: trucksales.na@kiongroup.com **linde-mh.us/automation** 



Member of KION Group